

Titan II

TITAN II is practically identical to TITAN I, containing all the safety, reliability and feature filled design but with the added benefit of having the option of using a second camera.

Internal, external, side/reverse, driver facing IR/Non-IR, heavy duty – almost any variety of 3rd party hardware can be utilised alongside the main TITAN II unit to make an adaptable and functional commercial system. Here at VIRTUS FLEET we are committed to improving driving behaviour standards and have developed the most up to date technology in vehicle safety solutions which can be epitomised in the TITAN collection



OPTIONAL CAMERAS



FULL HD 1080 1920x1080 FULL HD IMAGE RECORDING

165° 165° WIDE ANGLE VIEW

TAMPER PROOF

LOW POWER CONSUMPTION

LOCKABLE

Model	Titan II
Channels	2
Camera	1 / 2.9" CMOS Digital
Second Camera	Internal/External 2.5mm jack NTSC AHD 4-Pin Aviation
Camera Angle (Main)	165°
Camera Angle (secondary)	Depends on camera selection
Recording Resolution	1920 x 1080 - 30fps
Recording modes	Driving, Parked, G-sensor, Emergency
Video Out	1x CVBS Output
GPS	Built in GPS
G-Sensor	Built in 3-Axis Acceleration Sensor
Memory card	8Gb - 128Gb MLC grade Micro SD Card
Maximum Recording Time	30 Hours Depending On Quality/Resolution Settings with 2 channels
Audio Recording	Built in High Sensitivity Microphone
Notifications	Built in High Quality Speaker
Battery Protection	Yes
PC Viewer	Yes - Password Protected
Power - Rated Voltage	DC 12v - 24v
Power - Operating Voltage	DC 7v - 28v
Power - Consumption	210 - 250mA
Operating Temperature	-10°C - 70°C
Storage Temperature	-30°C - 80°C
Additional Features	Tamperproof, Uses Format Free Technology, Video Zoom Window, Low Profile Design, Auto Shutdown Timer, 8x Event types for Specific Alerts, Trigger Output for Tracker integration

